

ADEGRIP ECO

Adhesion primer based on dispersion polymers, free of solvents



Technical features

Super adhesive primer based on dispersion polymers and selected sands, free of solvents, with very low emission of Volatile Organic Compounds (VOC), to be used indoors and outdoors, on walls and floors, as bonding layer on non-absorbing, smooth and compact substrates before applying self-levelling grouts, smoothing or bonding products for ceramics and natural stones.

Applications

Preparation of substrates made up of glazed ceramic, marbles and natural stones, levelled concrete (and/or treated with epoxy paints), residues of old adhesives (for wood, PVC, carpet, linoleum), chipboard and multi-layer panels, de-waxed well fixed parquet, metal.

Important warnings

Avoid dirtying and walking on the applied coat of primer ADEGRIP ECO. Do not use ADEGRIP ECO at temperatures lower than + 5°C or higher than + 30°C.

Substrate preparation

Before the application, check the substrate is clean, solid, free of crumbling parts and without grease, oils, paints and dust.

Application

Mix the product before using it and apply a thin layer by brush or roller. After the primer has dried (approx. 15 to 60 minutes depending on the environmental conditions) the following application can be made respecting the instructions on the material to be applied.

Cleaning

Wash tools and hands with water, before the product has dried.

Specifications

To improve the adhesion on smooth and compact substrates, use an adhesion primer in water dispersion with very low content of Volatile Organic Compounds (VOC), e.g. ADEGRIP ECO by ADESITAL S.p.A.

Technical data (at +23°C and 50% R.H.)

Appearance	creamy liquid
Colour	grey
Storage	24 months in the original packaging
	Protect against frost
Hazard data	none
	Please check the information on the package
	and on the safety sheet
Flammability	no

Application data

Application temperature	from + 5°C to + 30°C
Time necessary before the following application	from 15 to 60 minutes

Coverage	200 - 300 g/m ²
----------	----------------------------

ADEGRIP ECO packages	5 kg drum
----------------------	-----------

Warning: The above indications and rules correspond to our best experience, but shall be deemed as merely indicative and shall be confirmed by exhaustive practical tests; thus, before using the product, the operator shall determine if it is suitable for its intended use and shall undertake every responsibility resulting from its use. PROFESSIONAL USE ONLY