

# Kemp Flowmon Collector Models

Valid from August 1, 2021



## Kemp Flowmon Collector

Kemp Flowmon Collector is a stand-alone appliance for collection, long-term storage and analysis of flow data (NetFlow, IPFIX, sFlow, and other standards compatible with NetFlow) from flow enabled devices (switches, routers), Kemp Flowmon Probes or other flow sources. All Kemp Flowmon Collector models are equipped with **Flowmon Monitoring Center (FMC)** – a tool for flow collection, viewing and analyzing, automatic reporting and more. Flowmon Monitoring Center provides complete visibility into network traffic through dashboards, long-term graphs with various perspectives, Top N statistics, user-defined profiles, possibility to drill-down to any communication and more. Kemp Flowmon Collector’s functionality can be extended with Kemp Flowmon modules.

Kemp Flowmon Collector is available in the form of a hardware appliance of 1U or 2U rack unit size and as a virtual appliance for deployment into virtual environments in VMware, Hyper-V, KVM, AWS, Azure or Google Cloud.



## Hardware Appliance

Kemp Flowmon Collector is equipped with two copper 10/100/1000 Mbps Ethernet **management ports** which can be used for appliance configuration, management and flow data collection. Management ports can be upgraded to 10 Gbps Ethernet ports by purchasing an upgrade package. The upgrade package can be purchased only for new appliances (at the moment of purchase).

Kemp Flowmon Collector is also equipped with a **remote control** feature for remote monitoring of device conditions. It offers command-line access, a web GUI and a virtual console. All hardware-based models provide a dedicated network interface for remote control. For details, see the Pre-installation Manual document available at <https://support.kemptechnologies.com/>.

Kemp Flowmon Collector models differ in storage capacity, type of RAID, performance and dimensions of the server (1U/2U).

## Virtual Appliance

Kemp Flowmon Collector in the form of a virtual appliance (VA) is designed for deployment into virtual and cloud environments (VMware, Hyper-V, KVM, AWS, Azure, Google Cloud) and **provides the same functionality as a hardware-based Kemp Flowmon Collector**. Kemp Flowmon Collector models differ in performance and storage capacity.

Kemp Flowmon Collector VA supports up to two **management ports** which can be used for appliance configuration, management and flow data collection.

In addition, a Kemp Flowmon Collector VA supports up to two 1 Gbps Ethernet **monitoring ports** which provide network traffic monitoring and flow data (NetFlow/IPFIX) production. Kemp Flowmon Collector VA enables network traffic monitoring in a virtual environment without the necessity for other appliances for flow data production.

## Distributed Architecture

Distributed architecture (DA) provides high scalability and load balancing for large and demanding environments with high volumes of flow data and a large number of flow sources. Flow data is distributed among multiple units for profiles computation and other flow data processing. More units can be simply added to increase both performance and storage capacity. Distributed Architecture provides a central console for management and configuration of all units in remote geographical locations as well as data aggregation and visualization in one place.

There are 3 types of units in DA: Master, Proxy and Slave units. **Master and Proxy units are dedicated hardware-based or virtual appliances**. Slave Units are traditional Kemp Flowmon Collectors (hardware-based or virtual appliances).

Find out more about Distributed Architecture in [Kemp Flowmon Distributed Architecture Overview](#).

## Hardware Appliances

P/N	Model	Performance (fps) <sup>1</sup>			Storage Capacity	RAID	Disk Type	CPU <sup>5</sup>	RAM	Form Factor
		Peak <sup>2</sup>	Moderate user experience <sup>3</sup>	Best user experience <sup>4</sup>						
<b>IFC-R5-1000</b>	Kemp Flowmon Collector R5-1000	75 000	40 000	20 000	1 TB	HW RAID5	3 x SATA Hot Swap	8	32 GB	1U
<b>IFC-R5-2000</b>	Kemp Flowmon Collector R5-2000	100 000	40 000	20 000	2 TB	HW RAID5	3 x SATA Hot Swap	8	32 GB	1U
<b>IFC-R5-3000PRO</b>	Kemp Flowmon Collector R5-3000 Pro	150 000	80 000	40 000	3 TB	HW RAID5	4 x SATA Hot Swap	32	64 GB	1U
<b>IFC-R10-4000PRO</b>	Kemp Flowmon Collector R10-4000 Pro	250 000	120 000	60 000	4 TB	HW RAID10	4 x SATA Hot Swap	32	64 GB	1U
<b>IFC-R5-6000PRO</b>	Kemp Flowmon Collector R5-6000 Pro	150 000	80 000	40 000	6 TB	HW RAID5	4 x SATA Hot Swap	32	64 GB	1U
<b>IFC-R5-12000PRO</b>	Kemp Flowmon Collector R5-12000 Pro	200 000	120 000	60 000	12 TB	HW RAID5	4 x SATA Hot Swap	64	128 GB	1U
<b>IFC-R10-16000PRO</b>	Kemp Flowmon Collector R10-16000 Pro	300 000	160 000	80 000	16 TB	HW RAID10	4 x SATA Hot Swap	64	128 GB	1U
<b>IFC-R5-24000PRO</b>	Kemp Flowmon Collector R5-24000 Pro	200 000	120 000	60 000	24 TB	HW RAID5	4 x SATA Hot Swap	64	128 GB	1U
<b>IFC-R6-48000PRO</b>	Kemp Flowmon Collector R6-48000 Pro	250 000	120 000	60 000	48 TB	HW RAID6	8 x SATA Hot Swap	72	128 GB	2U
<b>IFC-R6-96000PRO</b>	Kemp Flowmon Collector R6-96000 Pro	250 000	120 000	60 000	96 TB	HW RAID6	14 x SATA Hot Swap	72	128 GB	2U
<b>IFC-R6-192000PRO</b>	Kemp Flowmon Collector R6-192000 Pro	250 000	120 000	60 000	192 TB	HW RAID6	18 x SATA Hot Swap	72	128 GB	2U
<b>IFC-R5-2880SSD</b>	Kemp Flowmon Collector R5-2880 SSD	400 000	200 000	100 000	2.88 TB	HW RAID5	4 x SATA Hot Swap	72	256 GB	1U
<b>IFC-R5-11400SSD</b>	Kemp Flowmon Collector R5-11400 SSD	400 000	200 000	100 000	11.4 TB	HW RAID5	4 x SATA Hot Swap	72	256 GB	1U
<b>IFC-MU</b>	Kemp Flowmon Collector – Master Unit		-		6 TB	HW RAID5	4 x SATA Hot Swap	32	64 GB	1U
<b>IFC-PU</b>	Kemp Flowmon Collector – Proxy Unit		-		6 TB	HW RAID5	4 x SATA Hot Swap	32	64 GB	1U

<sup>1</sup> Performance is measured in our test environment using average customer data. There are several factors that may affect your specific performance, such as enabled extensions and modules or the number of concurrently executed queries in FMC. While we do our best to represent the data as fairly and accurately as possible, your environment may experience different limits.

<sup>2</sup> The maximum number of flows per second (fps) that a Kemp Flowmon Collector optimized for flow collection can process. In this setup, no optional features are enabled and no other modules are in use.

<sup>3</sup> This setup represents a good balance between performance and user experience while using optional features or Flowmon modules.

<sup>4</sup> This setup ensures the best user-experience in complex network environments while using all features, or running multiple Flowmon modules.

<sup>5</sup> Number of CPU cores, with Hyper Threading enabled.

## Hardware Appliances – Operating conditions

P/N	Model	Dimensions (H x W x D) cm	Weight (kg)	PSU		Power Consumption		Heat Dissipation (max.)
				Power	Hot Swap	CPU Idle	CPU max	
<b>IFC-R5-1000</b>	Kemp Flowmon Collector R5-1000	4.3 x 43.4 x 57.3	12.2	450 W	no	94 W	184 W	1039 BTU/h
<b>IFC-R5-2000</b>	Kemp Flowmon Collector R5-2000	4.3 x 43.4 x 57.3	12.2	450 W	no	94 W	184 W	1039 BTU/h
<b>IFC-R5-3000PRO</b>	Kemp Flowmon Collector R5-3000 Pro	4.3 x 43.4 x 69.3	17.6	2 x 550 W	yes	130 W	303 W	2559 BTU/h
<b>IFC-R10-4000PRO</b>	Kemp Flowmon Collector R10-4000 Pro	4.3 x 43.4 x 69.3	17.6	2 x 550 W	yes	130 W	303 W	2559 BTU/h
<b>IFC-R5-6000PRO</b>	Kemp Flowmon Collector R5-6000 Pro	4.3 x 43.4 x 69.3	17.6	2 x 550 W	yes	130 W	303 W	2559 BTU/h
<b>IFC-R5-12000PRO</b>	Kemp Flowmon Collector R5-12000 Pro	4.3 x 43.4 x 69.3	17.6	2 x 550 W	yes	144 W	357 W	2559 BTU/h
<b>IFC-R10-16000PRO</b>	Kemp Flowmon Collector R10-16000 Pro	4.3 x 43.4 x 69.3	17.6	2 x 550 W	yes	144 W	357 W	2559 BTU/h
<b>IFC-R5-24000PRO</b>	Kemp Flowmon Collector R5-24000 Pro	4.3 x 43.4 x 69.3	17.6	2 x 550 W	yes	144 W	357 W	2559 BTU/h
<b>IFC-R6-48000PRO</b>	Kemp Flowmon Collector R6-48000 Pro	8.7 x 43.4 x 68.2	25.4	2 x 1100 W	yes	180 W	351 W	4100 BTU/h
<b>IFC-R6-96000PRO</b>	Kemp Flowmon Collector R6-96000 Pro	8.7 x 43.4 x 71.6	33.1	2 x 1100 W	yes	358 W	445 W	4100 BTU/h
<b>IFC-R6-192000PRO</b>	Kemp Flowmon Collector R6-192000 Pro	8.7 x 43.4 x 71.6	33.1	2 x 1100 W	yes	403 W	494 W	4100 BTU/h
<b>IFC-R5-2880SSD</b>	Kemp Flowmon Collector R5-2880 SSD	4.3 x 43.4 x 69.3	17.6	2 x 550 W	yes	144 W	357 W	2559 BTU/h
<b>IFC-R5-11400SSD</b>	Kemp Flowmon Collector R5-11400 SSD	4.3 x 43.4 x 69.3	17.6	2 x 550 W	yes	144 W	357 W	2559 BTU/h
<b>IFC-MU</b>	Kemp Flowmon Collector – Master Unit	4.3 x 43.4 x 69.3	17.6	2 x 550 W	yes	130 W	303 W	2559 BTU/h
<b>IFC-PU</b>	Kemp Flowmon Collector – Proxy Unit	4.3 x 43.4 x 69.3	17.6	2 x 550 W	yes	130 W	303 W	2559 BTU/h

### Continuous Operation:

- Temperature: 10°C ÷ 35°C
- Relative Humidity<sup>1</sup>: 10% ÷ 80% at 29°C

### Expanded Operation<sup>2</sup>:

- Temperature: 5°C ÷ 40°C
- Relative Humidity<sup>1</sup>: 5% ÷ 85% at 29°C

<sup>1</sup> The specified temperature is the maximum dew point temperature.

<sup>2</sup> When operating in the expanded temperature range, system performance may be impacted. Device can work in this condition for up to 1% of annual operating hours.

## Virtual Appliances

P/N	Model	Performance (fps) <sup>1,2</sup>	Storage Capacity <sup>3</sup>	VMware ESXi	Windows Hyper-V	KVM	Minimum Configuration <sup>3</sup>
<b>IFC-500-VA</b>	Kemp Flowmon Collector 500 Virtual Appliance	up to 75 000	0.5 TB	5.5 and higher	2012 R2 and higher	KVM 3.10.0 and higher QEMU 1.5.3 and higher libvirt 4.5.0 and higher	2 CPU cores, 8 GB RAM, 500 IOPS
<b>IFC-1000-VA</b>	Kemp Flowmon Collector 1000 Virtual Appliance	up to 75 000	1 TB				2 CPU cores, 8 GB RAM, 500 IOPS
<b>IFC-2000-VA</b>	Kemp Flowmon Collector 2000 Virtual Appliance	up to 75 000	2 TB				2 CPU cores, 8 GB RAM, 500 IOPS
<b>IFC-3000-VA</b>	Kemp Flowmon Collector 3000 Virtual Appliance	up to 150 000	3 TB				4 CPU cores, 8 GB RAM, 1000 IOPS
<b>IFC-6000-VA</b>	Kemp Flowmon Collector 6000 Virtual Appliance	up to 150 000	6 TB				4 CPU cores, 8 GB RAM, 1000 IOPS
<b>IFC-12000-VA</b>	Kemp Flowmon Collector 12000 Virtual Appliance	up to 200 000	12 TB				8 CPU cores, 16 GB RAM, 2000 IOPS
<b>IFC-24000-VA</b>	Kemp Flowmon Collector 24000 Virtual Appliance	up to 200 000	24 TB				8 CPU cores, 16 GB RAM, 2000 IOPS
<b>IFC-48000-VA</b>	Kemp Flowmon Collector 48000 Virtual Appliance	up to 200 000	48 TB				8 CPU cores, 16 GB RAM, 2000 IOPS
<b>IFC-64000-VA</b>	Kemp Flowmon Collector 64000 Virtual Appliance	up to 200 000	64 TB				8 CPU cores, 16 GB RAM, 2000 IOPS
<b>IFC-VA-MU</b>	Kemp Flowmon Collector VA – Master Unit	–	6 TB	5.5 and higher	2012 R2 and higher	KVM 3.10.0 and higher QEMU 1.5.3 and higher libvirt 4.5.0 and higher	4 CPU cores, 8 GB RAM, 1000 IOPS
<b>IFC-VA-PU</b>	Kemp Flowmon Collector VA – Proxy Unit	–	6 TB				4 CPU cores, 8 GB RAM, 1000 IOPS

<sup>1</sup> The maximal measured performance in flows per second (fps).

<sup>2</sup> Performance is measured in our test environment using average customer data. In virtual environments, the performance depends on allocated resources, overall system load, and environment of deployment. There are several other factors that may affect your specific performance, such as enabled extensions and modules or the number of concurrently executed queries in FMC. While we do our best to represent the data as fairly and accurately as possible, your environment may experience different limits. Maximal performance can be achieved by allocating a sufficient amount of **dedicated** hardware resources, see Hardware Appliances for reference.

<sup>3</sup> Some configuration options, such as supported disk size, may be limited by the customer's virtual environment regardless of which Kemp Flowmon Collector model has been selected. Any such limitations should be consulted with the vendor/distributor of the virtual environment.