



Premier Surface

Entrance tiles designed to be laid directly to the floor surface

No matwell required, interlocking entrance tiles can be laid to surface. • Solid surface tiles effectively capture dirt to protect interior floors. • Hardwearing nylon carpet inserts scrape dirt and wipe moisture. • Suitable for high volume footfall in commercial locations. • Optional 'impact-resistant' bevelled edges and corners and T-pieces withstand heavy shopping trolleys. • Co-ordinating Alba carpet can also be supplied in rolls for primary and secondary dirt barrier use. • Fire tested to BS EN 13501-1 and slip tested to BS 7676-2. • Product Height: 12 mm



Size	Anthracite	Blue	Brown	Grey
30 cm x 30 cm	PSC010101	PSC010201	PSC010501	PSC010601

Edging	Black
Edging: 78 mm x 2.0 m lengths	PSE00002
Corners: 100 mm x 100 mm	PSC00004



Treadwell

100% recycled, hardwearing entrance floor tiles

Ideal for entrances with medium to high footfall. • Fit for use with trolleys. • Entrance floor tile manufactured from 100% recycled material. • Looks stylish when laid in uniform or parquet. • Easy to install. • Can be used for zone 1 to 3 in an entrance matting system. • Product Height: 10 mm

Size	Natural
305 mm x 305 mm (Pack of 10)	TW050001

