

HOFTRONIC™

DATASHEET LED PANEL 30X120CM 3000K

125 LM/WATT



Specifications	SKU 5434426	SKU 460447	SKU 557512	SKU 557505	SKU 557529
Watts	36 Watt	36 Watt	36 Watt	36 Watt	36 Watt
Equivalent watts	150 Watt	150 Watt	150 Watt	150 Watt	150 Watt
Luminous flux	4500 Lumen	4500 Lumen	4500 Lumen	4500 Lumen	4500 Lumen
Light color	Warm white	Warm white	Warm white	Warm white	Warm white
Color temperature	3000K	3000K	3000K	3000K	3000K
Color rendering index (CRI)	>80	>80	>80	>80	>80
Beam angle	120°	120°	120°	120°	120°
Input power	200-240V AC	200-240V AC	200-240V AC	200-240V AC	200-240V AC
Output power	27-42V DC	27-42V DC	27-42V DC	27-42V DC	27-42V DC
Powerfactor	>0.9	>0.9	>0.9	>0.9	>0.9
Driver	Yes	Yes	Yes	Yes	Yes
Dimmable	Yes	Yes, depending on driver	Yes, depending on driver	Yes, depending on driver	Yes, depending on driver
Material	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Shape	Rectangle	Rectangle	Rectangle	Rectangle	Rectangle
Frame color	White	White	White	White	White
IP-rate	IP20	IP20	IP20	IP20	IP20
Dimensions	295 x 1195 x 30 mm	295 x 1195 x 30 mm	295 x 1195 x 30 mm	295 x 1195 x 30 mm	295 x 1195 x 30 mm
Operating temperature	-20°C ~ 48°C	-20°C ~ 48°C	-20°C ~ 48°C	-20°C ~ 48°C	-20°C ~ 48°C
Certification	CE, EMC, RoHS, TÜV	CE, EMC, RoHS, TÜV	CE, EMC, RoHS, TÜV	CE, EMC, RoHS, TÜV	CE, EMC, RoHS, TÜV
Including light source	Yes	Yes	Yes	Yes	Yes
Energy label	A++	A++	A++	A++	A++
Life span	50.000 hours	50.000 hours	50.000 hours	50.000 hours	50.000 hours
Warranty	5 years	5 years	5 years	5 years	5 years
EAN	8720365434426	7439628460447	7439628557512	7439628557505	7439628557529

