

The Industrial Handset for Harsh Conditions in an Industrial Environment



FC11 DECT Industrial Handset

With its sturdy industrial housing, the Funktel FC11 easily withstands high pressure or falls from great heights (tested up to 1,8m on concrete). The handset is dust-proof and waterproof (IP 65 - compliant), allowing for outdoors use as well as use in harsh industrial environments.

The sturdy belt clip ensures secure support and great carrying comfort, while the bright 2-inch screen's crystal clear display guarantees best visibility even in unfavourable lighting conditions. The strong vibrator for hazard alarms and a discrete emergency call button each guarantee the highest level of protection in everyday use.

Device settings can be imported via MEM card directly from the FC1, D3 and FC4 series handsets without manual configuration being required. A comprehensive range of accessories and spare parts with rechargeable batteries, headsets as well as various pouches are available.

Features:

- GAP compatible
- Enhanced fall protection
- Dust- and waterproof (IP 65)
- Rechargeable Li-ion battery, screw-fastened
- Up to 200 hours stand-by
- Abrasion-resistant, illuminated keypad
- Bright 2-inch colour display
- Navigation rocker and programmable softkeys
- LED signal and counter for unread events



FC11 DECT Industrial Handset

Technical Data		
Size	Dimensions (L x W x H) :	Ca. 142 x 46 x 31 mm*
	Weight (with Battery) :	Ca. 121g**
	Screen :	2" TFT, 64k colours, 220 x 176 pixels
Degree of Protection and Temperature ranges	IP Protection Class :	IP65
	Operating temperature:	Handset : -10 ... +55°C Charger : +5 ...+40°C
	Storage temperature:	-25 ... +55°C (max. 1 month) 0 ...+25°C (max. 12 months)
	Shipping temperature:	-20 ... +60°C (with battery)
Power Supply	Li-ion battery:	1000 mAh
	Charging time:	Approx. 7h
Battery life	Standby:	Up to 200h
	Continuous conversation:	Up to 20h
DECT	Frequency range:	1,88 ... 1,9GHz
	Transmit power:	Average value 10 mW Peak value 250 mW
Acoustics	Acoustic signalling:	Max. 98 dB (A) in 30 cm distance***

*) including clip

**) including battery and clip

***) Depending on the selected ring tone, suitable for use in noisy environments