

PKB cable ties

DOUBLE LOCKING

- Easy to use with Partex cable markers, holders and sleeves.
- Double locking mechanism, on both sides, for maximum performance and reliability
- Manufactured of special UV-resistant polyamide, for extreme outdoor applications
- UL94V-2



Technical information

Material

Polyamide 6.6 UV stabilized (black)
Tooth: AISI 316 stainless steel

Halogen free
UL recognized: UL94V-2

Color

Black

Temperature

Installation temp. -40°C to +60°C.
Working temp. -40°C to +85°C.

Resistance

Excellent resistance to aromatic solvents, oils, greases and derivatives. Good resistance to bases.

Approvals/Certifications

EC Directives

The materials used to produce the cable ties comply with EC Directives: - 1907/2006/CE (REACH)

The materials are tested in accordance with EN 45545-2 «Railway applications - Fire protection on railway vehicles'. Part 2: Requirements for fire behavior of materials and components».

The materials are tested in accordance with IEC 60092-101 «Electrical installations in ships - Part 101: Definitions and general requirements».

Product conformity

The products are tested in accordance with CEI EN 62275 «Cable management systems - Cable ties for electrical installations».

The UV resistance of the products was tested according to ISO 4892-2 «Plastics - Methods of exposure to laboratory light sources - Part 2: Xenon-arc lamps».

Product information

Article number	Length (mm)	Width (mm)	Max bundle diameter (mm)	Tensile strength (N)	Qty per bag
PKB25100A0MBDL	100	2,5	21	150	100 pcs
PKB25200A0MBDL	200	2,5	50	150	100 pcs
PKB35140A0MBDL	140	3,5	35	250	100 pcs
PKB35295A0MBDL	295	3,5	80	250	100 pcs
PKB35205A0MBDL	205	3,5	50	250	100 pcs
PKB45200A0MBDL	200	4,5	50	360	100 pcs
PKB45255A0MBDL	255	4,5	68	360	100 pcs
PKB45290A0MBDL	290	4,5	80	360	100 pcs
PKB45365A0MBDL	365	4,5	101	360	100 pcs
PKB75220A0MBDL	220	7,5	55	780	100 pcs
PKB75360A0MBDL	360	7,5	100	780	100 pcs