

PKB cable ties

- Easy to use with Partex cable markers, holders and sleeves.
- UV resistance (black cable tie)
- UL94V-2
- Compliant with UNI EN 45545-2:2020



Technical information

Design

Self-locking cable ties with specially designed end for easier insertion into the lock and the Partex punched cable marking.

Material

Polyamide 6.6 (halogen free)
Tooth: AISI 316 stainless steel

Color

Black, Natural

Temperature

Installation temp. -10°C to +60°C.
Working temp. -40°C to +85°C.

Resistance

Excellent resistance to aromatic solvents, oils, greases and derivatives.

Approvals/Certifications

EC Directives

The materials used to produce the cable ties comply with EC Directives: - 1907/2006/CE (REACH)

The materials are tested in accordance with EN 45545-2 «Railway applications - Fire protection on railway vehicles'. Part 2: Requirements for fire behavior of materials and components».

The materials are tested in accordance with IEC 60092-101 «Electrical installations in ships - Part 101: Definitions and general requirements».

Product conformity

The products are tested in accordance with CEI EN 62275 «Cable management systems - Cable ties for electrical installations».

Product information

Article no black	Article no natural	Length (mm)	Width (mm)	Max bundle diameter (mm)	Tensile strength (N)	Qty per bag
PKB25098A0T	PKB25098A9T	98	2,5	21	80	100 pcs
PKB25135A0T	PKB25135A9T	135	2,5	32	80	100 pcs
PKB26200A0T	PKB26200A9T	200	2,6	51	80	100 pcs
PKB35140A0T	PKB35140A9T	140	3,5	32	180	100 pcs
PKB35200A0T	PKB35200A9T	200	3,5	50	180	100 pcs
PKB35290A0T	PKB35290A9T	290	3,5	79	180	100 pcs
PKB45160A0T	PKB45160A9T	160	4,5	38	220	100 pcs
PKB45200A0T	PKB45200A9T	200	4,5	50	220	100 pcs
PKB45290A0T	PKB45290A9T	290	4,5	78	220	100 pcs
PKB45360A0T	PKB45360A9T	360	4,5	100	220	100 pcs
PKB45390A0T	PKB45390A9T	390	4,5	106	220	100 pcs
PKB45430A0T	PKB45430A9T	430	4,5	115	220	100 pcs
PKB75300A0T	PKB75300A9T	300	7,5	80	540	100 pcs
PKB75365A0T	PKB75365A9T	365	7,5	100	540	100 pcs
PKB75450A0T	PKB75450A9T	450	7,5	130	540	100 pcs
PKB75540A0T	PKB75540A9T	540	7,5	158	540	100 pcs
PKB75750A0T	PKB75750A9T	750	7,5	220	700	100 pcs
PKB90780A0T	PKB90780A9T	780	9,0	233	1080	100 pcs
PKB125500A0T	PKB125500A9T	500	12,5	143	1080	50 pcs
PKB1251000A0T	PKB1251000A9T	1000	12,5	302	1080	50 pcs