

Product Technical Data Sheet:

Marker Cable Ties

Description


Partex marker cable ties provide a quick and effective method for securing and identifying bundles of cables. They can also be used to mark components and pipe work. They can be marked using the Partex indelible marker pen, or by attaching a printed self adhesive label to the marker tag.

Specification

Material:	DuPont Zytel 101F Nylon 6.6 Polyamide
Flammability:	Self-extinguishing to UL 94-V2
Work Temperature:	-40°C to +85°C
Recommended storage conditions:	+15°C to +30°C 50% Humidity.

High tension, highly resistant against; Brake Fluids, Lubricants, Power Steering Fluids, Oil, Grease, Paints, Lacquer Detergents, Animal and Vegetable Fats, Alkali up to 40% and Gasoline.


Three types are available.



Partex Part No	Length (mm)	Width (mm)	Maximum Bundle (mm)	Tensile Strength (kg)	Marking Pad Size LxW (mm)	Available Colours
MAR100F	98	2.5	20	8	8 x 25	Natural
MAR110F	110	2.5	20	8	9 x 20	Natural
MAR200W *	194	4.8	45	22	27 x 13	Nat/Yellow

UL: Cable ties are listed by the Underwriters laboratory, File number E475484.

Items marked * are pending approval.



Partex Marking Systems (UK) LTD

61-64 Station Road, Coleshill, Birmingham B46 1JT

Tel: 01675 463670 Fax: 01675 463520 Email: sales@partex.co.uk



Issue 3
November 2015

www.partex.co.uk

