

Product Technical Data Sheet:

Screw Mount Cable Ties



Description

Partex screw mount cable ties can be screwed or bolted down to provide a quick and effective method for securing cables to a panel or other surface.


Specification

Material: DuPont Zytel 101F Nylon 6.6 Polyamide
 Flammability: Self-extinguishing to UL94-V2
 Work Temperature: -40°C to +85°C
 Recommended storage conditions: +15°C to +30°C 50% Humidity.

High tension, highly resistant against; Brake Fluids, Lubricants, Power Steering Fluids, Oil, Grease, Paints, Lacquer Detergents, Animal and Vegetable Fats, Alkali up to 40% and Gasoline.

Partex	Length	Width	Maximum	Tensile	Size of	Available
Part No	(mm)	(mm)	Bundle (mm)	Strength (kg)	Screw	Colours
MT110 *	110	2.5	18	8	M3	Natural
MT150	150	3.6	32	18	M4	Natural
MT200	200	4.8	50	22	M5	Natural/Black
MT300 *	305	7.6	76	55	M6	Natural/Black

UL: Cable ties are listed by the Underwriters laboratory, File number E475484.
 Items marked * are pending approval.



Partex Marking Systems (UK) LTD

61-64 Station Road, Coleshill, Birmingham B46 1JT

Tel: 01675 463670 Fax: 01675 463520 Email: sales@partex.co.uk