



+ INFORMATION

HF - Halogen Free Printable Heat Shrink Sleeves

Very flexible, low smoke, zero halogen and flame retardant heat shrinkable tubing (2:1 shrink ratio). Flexible polyolefin sleeves used for wire identification. Offers excellent fire safety characteristics combined with minimal smoke emissions.

- + Flame Retardant to UL224 VW-1
- + Low Smoke
- + Zero Halogen
- + Easy Pick Application
- + Backing card perforated after every sleeve
- + Print performance to Military Specifications
- + RoHS and REACH Compliant

+ SPECIFICATIONS

Temperature range
-30°C to +105°C

Material
flexible polyolefin

Print
thermal transfer

Standard colours
yellow and white

Shrink ratio
2:1

Certified and issued to:
UL224 VW-1 Flammability

Print performance to military specifications
Adherence: SAE-AS81531-1998 Clause 4.6.2
Fluid Resistance: MIL202 Method 215K

+ PROPERTIES

PROPERTY	VALUE
Continuous Operating Temperature	-30°C to +105°C
Elongation After Heat Ageing (150°C x 168h)	250% Min.
Heat Shock (225°C x 4h)	No cracking, flowing or dripping
Min. Shrink Temp. for full Recovery	+90°C
Longitudinal Change	+5%, -10% Max.
Tensile Strength	13.0 MPa Min.
Elongation at Break	400% Min.
Oxygen Index	36%
Dielectric Strength	20kV/mm
Volume Resistivity	1014 ohm cm

+ RELATED PRODUCTS



MK10
PAGE 108



MK10-DH
PAGE 110



EOS1
PAGE 106



RIBBONS
PAGE 81

PROSLEEVE - HF
HALOGEN FREE

+ PRODUCT RANGE

TYPE	DIAMETER [mm] BEFORE SHRINKING	DIAMETER [mm] AFTER SHRINKING	SLEEVE LENGTH [mm]	MARKERS ACCROSS	MARKERS / BOX
HF^024125LR*	2.4	1.2	12.5	4	4000
HF^024250LR*	2.4	1.2	25	2	2000
HF^024500LR*	2.4	1.2	50	1	1000
HF^032125LR*	3.2	1.6	12.5	4	4000
HF^032250LR*	3.2	1.6	25	2	2000
HF^032500LR*	3.2	1.6	50	1	1000
HF^048125LR*	4.8	2.4	12.5	4	4000
HF^048250LR*	4.8	2.4	25	2	2000
HF^048500LR*	4.8	2.4	50	1	1000
HF^064125LR*	6.4	3.2	12.5	4	4000
HF^064250LR*	6.4	3.2	25	2	2000
HF^064500LR*	6.4	3.2	50	1	1000
HF^095125LR*	9.5	4.75	12.5	4	2000
HF^095250LR*	9.5	4.75	25	2	1000
HF^095500LR*	9.5	4.75	50	1	500
HF^127125LR*	12.7	6.4	12.5	4	2000
HF^127250LR*	12.7	6.4	25	2	1000
HF^127500LR*	12.7	6.4	50	1	500
HF^190125LR*	19.0	9.5	12.5	4	2000
HF^190250LR*	19.0	9.5	25	2	1000
HF^190500LR*	19.0	9.5	50	1	500
HF^254250LR*	25.4	12.7	25	2	600
HF^254500LR*	25.4	12.7	50	1	300
HF^381500LR*	38.1	19.1	50	1	100
HF^508500LR*	50.8	25.4	50	1	100

^ = S (single sided), D (double sided); * = Colour (4=Yellow, 9=White)
Recommended ribbon: 2020 or 510 series