



INFORMATION

- + Flame Retardant
- + Self Extinguishing
- + Meets NSA 937201 Specification
- + Easy Pick Application
- + Perforation after every sleeve for easy sorting
- + Print performance to Military Specifications

Temperature range

-55°C to +135°C

Material

flexible polyolefin

Print

thermal transfer

Print performance

Adherence: SAE-AS5942

Fluid Resistance: MIL202 Method 215J

Standard colours

yellow and white

Shrink ratio

3:1

Certified and issued to:

SAE-AMS-DTL-23053/5

UL224 VW-1 Flammability

NSA 937201MR

NSA 937201MT

DIMENSIONS | PACKAGING

TYPE	DIAMETER [D mm]	DIAMETER [D1 mm]	SLEEVE LENGTH [mm]	MARKERS ACCROSS	MARKERS / BOX
MS^024125LR*	2.4	0.8	12.5	4	4000
MS^024250LR*	2.4	0.8	25	2	2000
MS^024500LR*	2.4	0.8	50	1	1000
MS^032125LR*	3.2	1.10	12.5	4	4000
MS^032250LR*	3.2	1.10	25	2	2000
MS^032500LR*	3.2	1.10	50	1	1000
MS^048125LR*	4.8	1.6	12.5	4	4000
MS^048250LR*	4.8	1.6	25	2	2000
MS^048500LR*	4.8	1.6	50	1	1000
MS^064125LR*	6.4	2.10	12.5	4	4000
MS^064250LR*	6.4	2.10	25	2	2000
MS^064500LR*	6.4	2.10	50	1	1000
MS^095125LR*	9.5	3.2	12.5	4	2000
MS^095250LR*	9.5	3.2	25	2	1000
MS^095500LR*	9.5	3.2	50	1	500
MS^127125LR*	12.7	4.2	12.5	4	2000
MS^127250LR*	12.7	4.2	25	2	1000
MS^127500LR*	12.7	4.2	50	1	500
MS^180125LR*	18.0	6.4	12.5	4	2000
MS^180250LR*	18.0	6.4	25	2	1000
MS^180500LR*	18.0	6.4	50	1	500
MS^254125LR*	25.4	8.5	12.5	4	1200
MS^254250LR*	25.4	8.5	25	2	600
MS^254500LR*	25.4	8.5	50	1	300
MS^381500LR*	38.1	19.1	50	1	100

^ = S (single sided), D (double sided)

* = Colour (4=Yellow, 9=White)