



+ INFORMATION

- + Flexible, round profile made of cross-linked heat shrinkable polyolefin.
- + Many applications in industry.
- + Excellent properties and fire safety characteristics.
- + Low smoke generation and evolution of acid gases.
- + 2:1 shrink ratio.

+ PROPERTIES

Temperature range
-55°C to +125°C

Material
polyolefin, flame retardant in accordance with ASTM D2671

Print
thermal transfer

Standard colours
yellow and white, other colours available on request

According to the standard
AMS-DTL-23053 Class 1
BS 6853:1999
CEN/TS 45545-2
UNI CEI 11170-3



PHZ20048BN4

+ DIMENSIONS AND PACKAGING



TYPE	DIAMETER [D mm]	DIAMETER [D1 mm]	THICKNESS [W mm]	PACKAGING	COMPATIBLE PRINTERS
PHZ20024	2.4	1.2	0.51	 15 m or 100 m	PROMARK-T1000
PHZ20032	3.2	1.6	0.51	 15 m or 100 m	
PHZ20048	4.8	2.4	0.51	 12 m or 100 m	
PHZ20064	6.4	3.2	0.64	 12 m or 100 m	
PHZ20095	9.5	4.8	0.64	 75 m	MK10, MK10-DH
PHZ20127	12.7	6.4	0.64	 50 m	
PHZ20190	19.0	9.5	0.77	 25 m	
PHZ20254	25.4	12.7	0.89	 25 m	
PHZ20381	38.1	19.1	1.02	 25 m	

+ RELATED PRODUCTS



PROMARK-T1000
▶ PAGE 102



MK10
▶ PAGE 108



MK10-DH
▶ PAGE 110

+ APPLICATION

