



### INFORMATION

- + Good resistance to scratching, smearing and rubbing
- + Excellent UV resistance on printed image
- + High tack adhesive, suitable for uneven surfaces
- + Easier and faster than engraved metal plates
- + Good resistance to alcohols and diesel oils
- + Glossy topcoat for a smart and professional look
- + ROHS and REACH Compliant

### SPECIFICATIONS

#### Material

Polyester tag based on a double sided adhesive tape with a compressible foam carrier and a permanent acrylic adhesive

#### Temperature range

Recommended Application Temperature 18 to 35 °C

Operating Temp. Foam -40°C to 100°C

Operating Temp. Polyester Film -40°C to 150°C

#### Print

thermal transfer

#### Print performance

STP-A3-S-NC-S

STP-EOS1-S-NC-S

#### Standard colours

yellow, white - other colours on request

#### Certified and issued to:

BS 3G198, Part 2, Type 7

### DIMENSIONS | PACKAGING

| TYPE        | HEIGHT | LENGTH | PACKAGING |
|-------------|--------|--------|-----------|
| EPL027008R* | 27 mm  | 8 mm   | 2500 pcs  |
| EPL027012R* | 27 mm  | 12 mm  | 2000 pcs  |
| EPL045015R* | 45 mm  | 15 mm  | 1500 pcs  |
| EPL069019R* | 69 mm  | 19 mm  | 1200 pcs  |
| EPL100050R* | 100 mm | 50 mm  | 500 pcs   |

\* = Colour (4=Yellow, 9=White)