



+ INFORMATION

- + A new, colourful touch screen.
- + Small table printer for high demand production of Partex PPQ, ProSleeve and other profiles.
- + Cost effective identification system for use in panel building and electrical installations.
- + Feeds and prints Partex profiles and labels.
- + Available also as mobile version, EOS5-MOBILE can be equipped with a battery.
- + EOS5 has possibility of placing small rolls of Partex profiles: PO/POZ, PHZF, PPQ and series of Prosleeve inside a printer housing.
- + It's very useful in field work or wherever markers are required and access to electrical connection is missing.
- + The printer is connected to the computer via a USB 2.0 port and controlled by Promark Creator software.
- + Wi-Fi module (optional).

+ PROPERTIES

Temperature range

Operating temperature: +5°C to +40°C

Humidity: 10 - 85 % not condensing

To obtain the best printing result, the temperature of the profile shouldn't be lower then +25°C

Thermal transfer printing

300 dpi print resolution

Power supply

100 - 240V (50-60Hz) max 300W.

CE - certified

PC connection

USB 2.0 connection and Promark Creator software.

Dimensions

245x264x412mm (H x W x D)

Printing speed

150 mm/s.

Weight

5,0 kg

+ PRINTER AND ACCESSORIES

ARTICLE NUMBER	INFORMATION	PACK UNIT (MOQ)
EOS5	Printer EOS5, USB cable, mains lead.	1 pce
MK-STV	Reel stand for small and bulk reels	1 pce
MK-RS3	Small reel stand, mountable	1 pce

