

CERTIFICATE

TÜV NORD CERT GmbH
herewith declares that

Viessmann Climate Solutions SE
Viessmannstrasse 1, 35108
Allendorf
Germany

is authorized to provide the product mentioned below with the mark as illustrated:



Description of product (details see Annex 2):

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules

Valid until: 2026-06-15

Certification program:	P12-VA-01 Rev. 17 09.20
Certification fundamental(s):	IEC 61701:2011 / EN 61701:2012 Severity 6.
Registered No.:	44 780 21 406749 - 131R2A1M2
Manufacturer:	see Annex 1
Test Report No.:	492011746.003
File No.:	PVP08191/23P-01



TÜV NORD CERT GmbH
Certification Body
Consumer Products

Essen, 2023-10-25

Please also pay attention to the information stated overleaf.

Description of product(s):

Module types:

PV Modules with Segmented 6" PERC Mono-crystalline Silicon Solar Cells

408 cells: Vitovolt 300 Mxxx WF (xxx = 460-505, in increment of 5)

408 cells: Vitovolt 300 Mxxx WF Allblack (xxx = 460-500, in increment of 5)

408 cells: Vitovolt 300 Mxxx WF Blackframe (xxx = 460-505, in increment of 5)

340 cells: Vitovolt 300 Mxxx WE (xxx = 380-420, in increment of 5)

340 cells: Vitovolt 300 Mxxx WK (xxx = 380-420, in increment of 5)

340 cells: Vitovolt 300 Mxxx WE Allblack (xxx = 380-415, in increment of 5)

340 cells: Vitovolt 300 Mxxx WK Allblack (xxx = 380-415, in increment of 5)

340 cells: Vitovolt 300 Mxxx WE Blackframe (xxx = 380-420, in increment of 5)

340 cells: Vitovolt 300 Mxxx WK Blackframe (xxx = 380-420, in increment of 5)

360 cells: Vitovolt 300 Mxxx WG (xxx = 370-400, in increment of 5)

360 cells: Vitovolt 300 Mxxx WG Allblack (xxx = 370-400, in increment of 5)

360 cells: Vitovolt 300 Mxxx WG Blackframe (xxx = 370-400, in increment of 5)

Maximum system voltage:

1500V

Fuse rating:

20A

Application class:

Class A

Electrical protection class:

Class II

Module types:

PV Modules with Segmented 8" PERC Mono-crystalline Silicon Solar Cells

345 cells: Vitovolt 300 Mxxx WI (xxx = 535-555, in increment of 5)

320 cells: Vitovolt 300 Mxxx WL (xxx = 425-445, in increment of 5)

320 cells: Vitovolt 300 Mxxx WL Blackframe (xxx = 425-445, in increment of 5)

320 cells: Vitovolt 300 Mxxx WL Allblack (xxx = 420-440, in increment of 5)

305 cells: Vitovolt 300 Mxxx WM (xxx = 405-425, in increment of 5)

305 cells: Vitovolt 300 Mxxx WM Blackframe (xxx = 405-425, in increment of 5)

305 cells: Vitovolt 300 Mxxx WM Allblack (xxx = 400-420, in increment of 5)



TÜV NORD CERT GmbH
Certification Body
Consumer Products

5)

Maximum system voltage: 1500V
Fuse rating: 30A or 25A
Application class: Class A
Electrical protection class: Class II

Module types: **PV Modules with Half-cut 7" PERC Mono-crystalline Silicon Solar Cells:**

144 cells: Vitovolt 300 Mxxx WR (xxx = 525-570, in increment of 5)

Maximum system voltage: 1500V
Fuse rating: 25A
Application class: Class A
Electrical protection class: Class II

Module types: **PV Modules with Half-cut 7" TOPCon Mono-crystalline Silicon Solar Cells:**

108 cells: Vitovolt 300 Mxxx WP (xxx = 395-440, in increment of 5)

108 cells: Vitovolt 300 Mxxx WP Blackframe (xxx = 395-440, in increment of 5)

108 cells: Vitovolt 300 Mxxx WP Allblack (xxx = 395-440, in increment of 5)

Maximum system voltage: 1500V
Fuse rating: 25A
Application class: Class A
Electrical protection class: Class II

Remark:

For detailed product information, please refer to test report.



TÜV NORD CERT GmbH
Certification Body
Consumer Products