Substitutive Declaration of the Notorius Act

(Art. 19 and Art. 47 of D.P.R. No. 445)

Subject: Generator Declaration of Compliance

I am Ma Lin, born in China on June 4, 1980 and residing in Italy, in Via Giuseppe Dessì 40, Rome, fiscal code MAXLNI80H04Z210D, acting as prosecutor for Huawei Technologies Italia S.r.l., aware of the criminal penalties for untrue statements and false documents (art. 76 of Dpr No. 445/2000), under its own responsibility

DECLARES

the following products comply with IEC 0-21: 2022-03 / V1: 2022-11 / V2:2024-01/ V2/EC:2024-03

Section A	**The following generators meet the requirements of IEC 0-21: 2022-03 / V1: 2022-11 / V2:2024-01/ V2/EC:2024-03**						
	Manufacturer's	HUAWEI TECHNOLOGIES Co. LTD., Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, China					
	Equipment type	Inverters for photovoltaic systems					
	Brand name	HUAWEI TECHNOLOGIES Co. LTD					
	# Phases	☐ Monophase ・ Three-phase Frequency: 50 Hz / 60 Hz Voltage: 220 Vac / 380 Vac; 230 Vac / 400 Vac					
	Primary energy used	÷Solar (see. RdP All. B) ・ Accumulation (see RdP All. Bbis) ☐ Wind power (see RdP All. B/Bter) ☐ Hydroelectric (see RdP All. B/Bter) ☐ CHP (see RdP All. B/Bter) ☐ Other:					
	Generator model	SUN2000-3KTL-M0 SUN2000-3KTL-M1	SUN2000-4KTL-M0 SUN2000-4KTL-M1	SUN2000-5KTL-M0 SUN2000-5KTL-M1	SUN2000-6KTL-M0 SUN2000-6KTL-M1	SUN2000-8KTL-M0 SUN2000-8KTL-M1	SUN2000-10KTL-M0 SUN2000-10KTL-M1
	Rated power	3 kW	4 kW	5 kW	6 kW	8 kW	10 kW
	The generator:	・ It is suitable for installation in plants with a power output greater than 11.08 kW ・ It can limit the Idc to 0.5% of rated current: ǂ uses a protection function sensitive to direct current ☐ uses a transformer operating at the mains frequency					
Section B	Interface protection system characteristics						
	Manufacturer's	HUAWEI TECHNOLOGIES Co. LTD					
	Model	SUN2000-3-10KTL-M0, SUN2000-3-10KTL-M1					
	Type	・ Integrated ☐ Not integrated					
Section C	Static Converter Features						
	Model of the static converter	SUN2000-3KTL-M0 SUN2000-3KTL-M1	SUN2000-4KTL-M0 SUN2000-4KTL-M1	SUN2000-5KTL-M0 SUN2000-5KTL-M1	SUN2000-6KTL-M0 SUN2000-6KTL-M1	SUN2000-8KTL-M0 SUN2000-8KTL-M1	SUN2000-10KTL-M0 SUN2000-10KTL-M1
	Static Converter Manufacturer	HUAWEI TECHNOLOGIES Co. LTD					
	Firmware version	SUN2000MAV100R001 and above					

Huawei Technologies Italia S.r.l.

100% owned by Huawei Technologies Cooperatief U.A.
C.S. €3,000,000 i.v.
CCIAA e P.IVA 04501190963
HUAWEI.ITALY@HUAWEIPEC.IT
www.huawei.com

Sede Legale, Amministrativa e Operativa Centrale, MILANO

Via Lorenteggio 240, Torre A,
20147 MILANO (MI)
Tel.: +39.02.39994.000

Sede Operativa, MILANO

Maxwell Research Center, Milan
Viale Martesana 12
20055 VIMODRONE (MI)
Tel.: +39.02.39994882

Raffaello Research Center, Milan
Via Santa Margherita 14/Via Silvio Pellico 7, 20121 MILANO (MI)

Sede Operativa, ROMA

Via Laurentina 449/Via del Serafico 89
00142 ROMA (RM)
Tel.: +39.06.64244.000

Altre Sedi Operative

PALERMO Tel: 39. 0916242090

	Converter Rated Power (PNINV)	3 kW	4 kW	5 kW	6 kW	8 kW	10 kW

Section E	**Batteries that can be used with the above static converters**			
	Brand name	**HUAWEI TECHNOLOGIES Co. LTD**		
	Technology	**Lithium Iron Phosphate (LiFePO4)**		
	Firmware version BMS	**FusionSolarDGV100R002 (LUNA2000-5KW-C0), V200R023 (LUNA2000-10KW-C1) and above**		
	Notes	**The maximum effective discharge power depends on the size of the inverter, see attached.**		
	Types	☐Bi-directional ☐Muno-directional		
	Models	*LUNA2000-5KW-C0, LUNA2000-5-E0*	LUNA2000-10KW-C1, LUNA2000-7-E1	LUNA2000-10KW-C1, LUNA2000-5-E1
	CUS module (kWh)	5	6,9	5
	BMS Firmware Version	V100R002	V200R023	V200R023
	# Modules	1-6	1-6	1-6
	Note: Batteries are not built into the inverter and must be installed according to local regulations.			

Section I	**References of test laboratories and their test reports (ROP)**		
	Method of choice	・ Tests performed by an accredited laboratory	☐ Tests carried out under the supervision of an institution certifier
	Test Reports (RdP)	RoP: see certificate No. U25-0181 attached report number:18TH0255-CEI 021_8	

Huawei Technologies Italia S.r.l.

100% owned by Huawei Technologies Cooperatief U.A.
C.S. €3,000,000 i.v.
CCIAA e P.IVA 04501190963
HUAWEI.ITALY@HUAWEIPEC.IT
www.huawei.com

Sede Legale, Amministrativa e Operativa Centrale, MILANO

Via Lorenteggio 240, Torre A,
20147 MILANO (MI)
Tel.: +39.02.39994.000

Sede Operativa, MILANO

Maxwell Research Center, Milan
Viale Martesana 12
20055 VIMODRONE (MI)
Tel.: +39.02.39994882

Raffaello Research Center, Milan
Via Santa Margherita 14/Via Silvio Pellico 7, 20121 MILANO (MI)

Sede Operativa, ROMA

Via Laurentina 449/Via del Serafico 89
00142 ROMA (RM)
Tel.: +39.06.64244.000

Altre Sedi Operative

PALERMO Tel: 39. 0916242090

	Issued by	**Accredited Lab:** **Bureau Veritas Consumer Products Services Germany GmbH**	
	Accreditation No	D-PL-12024-03-04, Ref. DIN EN ISO/IEC 17025	
	Ref. Accreditation Institution	**DAkkS**	
Section L	**Date, signature**		
	Location, date	***Company*** ***Name, Signature, Function***	Lin Ma Huawei Technologies Italia S.r.l. Procuratore 13.02.2026 15:34:31 GMT+01:00

ANNEX I
Features Huawei LUNA2000-S1 Storage System

Energy Storage Module	SUN2000-3K-M1	SUN2000-4K-M1	SUN2000-5K-M1	SUN2000-6K-M1	SUN2000-8K- M1	SUN2000-10K-M1
	Psmax/Pcmax(W)					
LUNA2000-5KW-C0*1 (LUNA2000-5-E0*1)	2500/2500	2500/2500	2500/2500	2500/2500	2500/2500	2500/2500
LUNA2000-5KW-C0*1 (LUNA2000-5-E0*2)	3000/3300	4000/4400	5000/5000	5000/5000	5000/5000	5000/5000
LUNA2000-5KW-C0*1 (LUNA2000-5-E0*3)	3000/3300	4000/4400	5000/5000	5000/5000	5000/5000	5000/5000
LUNA2000-5KW-C0*2 (LUNA2000-5-E0*2)	3000/3300	4000/4400	5000/5000	5000/5000	5000/5000	5000/5000
LUNA2000-5KW-C0*2 (LUNA2000-5-E0*3)	3000/3300	4000/4400	5000/5500	6000/6600	7500/7500	7500/7500
LUNA2000-5KW-C0*2 (LUNA2000-5-E0*4)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-5KW-C0*2 (LUNA2000-5-E0*5)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-5KW-C0*2 (LUNA2000-5-E0*6)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*1 (LUNA2000-7-E1*1)	3000/3300	3500/3500	3500/3500	3500/3500	3500/3500	3500/3500
LUNA2000-10KW-C1*1 (LUNA2000-7-E1*2)	3000/3300	4000/4400	5000/5500	6000/6600	7000/7000	7000/7000
LUNA2000-10KW-C1*1 (LUNA2000-7-E1*3)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-7-E1*2)	3000/3300	4000/4400	5000/5500	6000/6600	7000/7000	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-7-E1*3)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-7-E1*4)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-7-E1*5)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-7-E1*6)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
Remark: Psn= Psmax= Pcn						

Huawei Technologies Italia S.r.l.

100% owned by Huawei Technologies Cooperatief U.A.
C.S. €3,000,000 i.v.
CCIAA e P.IVA 04501190963
HUAWEI.ITALY@HUAWEIPEC.IT
www.huawei.com

Sede Legale, Amministrativa e Operativa Centrale, MILANO

Via Lorenteggio 240, Torre A,
20147 MILANO (MI)
Tel.: +39.02.39994.000

Sede Operativa, MILANO

Maxwell Research Center, Milan
Viale Martesana 12
20055 VIMODRONE (MI)
Tel.: +39.02.39994882

Raffaello Research Center, Milan
Via Santa Margherita 14/Via Silvio Pellico 7, 20121 MILANO (MI)

Sede Operativa, ROMA

Via Laurentina 449/Via del Serafico 89
00142 ROMA (RM)
Tel.: +39.06.64244.000

Altre Sedi Operative

PALERMO Tel: 39. 0916242090

Battery module model	SUN2000-3K-M1	SUN2000-4K-M1	SUN2000-5K-M1	SUN2000-6K-M1	SUN2000-8K- M1	SUN2000-10K-M1
	Psmax/Pcmax(W)					
LUNA2000-10KW-C1*1 (LUNA2000-5-E1*1)	3000/3300	3500/3500	3500/3500	3500/3500	3500/3500	3500/3500
LUNA2000-10KW-C1*1 (LUNA2000-5-E1*2)	3000/3300	4000/4400	5000/5500	6000/6600	7000/7000	7000/7000
LUNA2000-10KW-C1*1 (LUNA2000-5-E1*3)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*2)	3000/3300	4000/4400	5000/5500	6000/6600	7000/7000	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*3)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*4)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*5)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*6)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
Remark: Psn= Psmax= Pcn						

Huawei Technologies Italia S.r.l.

100% owned by Huawei Technologies Cooperatief U.A.
C.S. €3,000,000 i.v.
CCIAA e P.IVA 04501190963
HUAWEI.ITALY@HUAWEIPEC.IT
www.huawei.com

Sede Legale, Amministrativa e Operativa Centrale, MILANO

Via Lorenteggio 240, Torre A,
20147 MILANO (MI)
Tel.: +39.02.39994.000

Sede Operativa, MILANO

Maxwell Research Center, Milan
Viale Martesana 12
20055 VIMODRONE (MI)
Tel.: +39.02.39994882

Raffaello Research Center, Milan
Via Santa Margherita 14/Via Silvio Pellico 7, 20121 MILANO (MI)

Sede Operativa, ROMA

Via Laurentina 449/Via del Serafico 89
00142 ROMA (RM)
Tel.: +39.06.64244.000

Altre Sedi Operative

PALERMO Tel: 39. 0916242090

Battery module model	SUN2000-3K-M1	SUN2000-4K-M1	SUN2000-5K-M1	SUN2000-6K- M1	SUN2000-8K-M1	SUN2000-10K-M1
Psmax/Pcmax(W)						
LUNA2000-10KW-C1*1 (LUNA2000-5-E1*1 & LUNA2000-7-E1*1)	3000/3300	3500/3500	5000/5500	6000/6600	7000/7000	7000/7000
LUNA2000-10KW-C1*1 (LUNA2000-5-E1*2 & LUNA2000-7-E1*1)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*1 (LUNA2000-5-E1*1 & LUNA2000-7-E1*2)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*1 & LUNA2000-7-E1*1)	3000/3300	4000/4400	5000/5500	6000/6600	7000/7000	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*1 & LUNA2000-7-E1*2)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*1 & LUNA2000-7-E1*3)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*2 & LUNA2000-7-E1*1)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*2 & LUNA2000-7-E1*2)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*2 & LUNA2000-7-E1*3)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*3 & LUNA2000-7-E1*1)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*3 & LUNA2000-7-E1*2)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*3 & LUNA2000-7-E1*3)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*1 & LUNA2000-7-E1*4)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*1 & LUNA2000-7-E1*5)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000
LUNA2000-10KW-C1*2 (LUNA2000-5-E1*2 & LUNA2000-7-E1*4)	3000/3300	4000/4400	5000/5500	6000/6600	8000/8800	10000/10000

Remark: Psn= Psmax= Pcn

Huawei Technologies Italia S.r.l.

100% owned by Huawei Technologies Cooperatief U.A.
C.S. €3,000,000 i.v.
CCIAA e P.IVA 04501190963
HUAWEI.ITALY@HUAWEIPEC.IT
www.huawei.com

Sede Legale, Amministrativa e Operativa Centrale, MILANO

Via Lorenteggio 240, Torre A,
20147 MILANO (MI)
Tel.: +39.02.39994.000

Sede Operativa, MILANO

Maxwell Research Center, Milan
Viale Martesana 12
20055 VIMODRONE (MI)
Tel.: +39.02.39994882

Raffaello Research Center, Milan
Via Santa Margherita 14/Via Silvio Pellico 7, 20121 MILANO (MI)

Sede Operativa, ROMA

Via Laurentina 449/Via del Serafico 89
00142 ROMA (RM)
Tel.: +39.06.64244.000

Altre Sedi Operative

PALERMO Tel: 39. 0916242090

Certificate of conformity

with the requirements of Standard IEC 0-21

Certifying Body Name	Bureau Veritas Consumer Products Services Germany GmbH Accreditation to DAkkS, D-ZE-12024-01-00, Ref. DIN EN ISO/IEC 17065
Subject	IEC 0-21: 2022-03 / V1: 2022-11 / V2:2024-01/ V2/EC:2024-03 Reference technical rule for the connection of active and passive users to LV networks of electricity distribution companies, Annex A: Characteristics and tests for the Protection Interface System (SPI), Annex B: Tests on grid-connected generators via static converters, Annex Bbis: Tests on storage systems

Typology of apparatus referred to and declaration

Device of interface	Protecting interface	Device of static conversion	Device of rotating generation
X	X	X	

Manufacturer's

Huawei Technologies Co., Ltd.
Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129
P.R.C

Primary energy used	Solar and Accumulation			
Equipment type	Inverters for photovoltaic systems and accumulator			
Generator model	SUN2000-3KTL-M0, SUN2000-3KTL-M1	SUN2000-4KTL-M0, SUN2000-4KTL-M1	SUN2000-5KTL-M0, SUN2000-5KTL-M1	SUN2000-6KTL-M0, SUN2000-6KTL-M1
Rated power [kW]	3	4	5	6
Generator model	SUN2000-8KTL-M0, SUN2000-8KTL-M1	SUN2000-10KTL-M0, SUN2000-10KTL-M1	Backup Box B1	--
Rated power [kW]	8	10	--	--

Firmware version V100R001

Number of phases Three-phase with neutral / Frequency 50Hz / Voltage 230V

Note the generator:
The device can limit the Idc to 0.5% of the rated current.
The device uses a protection function sensitive to direct current The device is suitable for installation in systems with a power output greater than 11.08 kW.
Huawei Technologies Co., Ltd. inverters have a maximum apparent power limit. If a plant must be able to reach a certain power factor in any working condition, the maximum active power must be set so that it can reach the φ volute cos at all times.

REFERENCES FROM LABORATORS WHICH HAVE DONE THE TESTS:

Bureau Veritas Consumer Products Services Germany GmbH Accreditation to DAkkS, D-PL-12024-03-04, Ref. DIN EN ISO/IEC 17025

Examined the ISO 9001 certificate of manufacturer No. 17 100 1933213, issued by TÜV Rheinland. Examined test dossier No.18TH0255-CEI 0-21_8, issued by Bureau Veritas Consumer Products Services Germany GmbH, Examined the manufacturer's CE declaration of conformity with the relevant test reports No.DM18110030 issued by STC Laboratory (Dongguan) Company Limited with accreditation recognized by DAkkS (No. D-PL-12121-01-00) It is declared that the product indicated complies with the requirements IEC 0-21: 2022-03, V1: 2022-11, V2: 2024-01/ V2/EC:2024-03, Annex A, Annex B and Annex Bbis.

Report number: 18TH0255-CEI 0-21_8
Certificate Number: U25-0181

Certification Program: NSOP-0032-DEU-ZE-V10
Date of issue: 2025-03-12

Certification body
Domenik Koll
Head of Energy Systems Germany

Accreditation
DAkkS Deutsche Akkreditierungsstelle D-ZE-12024-01-00

Accredited certification body by Deutsche Akkreditierungsstelle GmbH (DAkkS) according to ISO/IEC 17065. The accreditation is valid only for the scope listed in the annex of accreditation certificates D-ZE-12024-01-00. The Deutsche Akkreditierungsstelle GmbH (DAkkS) is signatory of the multilateral arrangements of EA, ILAC and IAF for mutual recognition. Without the written permission of Bureau Veritas Consumer Products Services Germany GmbH excerpts of this certificate of conformity shall not be reproduced. Bureau Veritas Consumer Products Services Germany GmbH Businesspark A96 certification.deu@bureauveritas.com

www.bureauveritas.de/unsere-services/produktzertifizierung 86842 Tuerkheimeee

Extract from test report 18TH0255-CEI 0-21_8 issued by a test laboratory accredited by "Deutsche Akkreditierungsstelle GmbH (DAkkS)" according to ISO/IEC 17025. The accreditation is only valid for the scope listed in the annex of accreditation certificates "D-PL-12024-03-04".

CEI 0-21: 2022-03 / V1: 2022-11 / V2: 2024-01/ V2/EC:2024-03 Reference technical rule for the connection of active and passive users to LV networks of energy distribution companies electric, Annex A: Interface Protection System (SPI) characteristics and tests. Annex B: Tests on grid-connected generators via static converters, Annex Bbis: Tests on storage systems	
Manufacturer of Protection System Interface (SPI)	Huawei Technologies Co., Ltd. Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129 P.R.C
Assigned to SUN2000-3KTL-M0, SUN2000-4KTL-M0,	SUN2000-5KTL-M0, SUN2000-6KTL-M0, SUN2000-8KTL-M0, SUN2000-10KTL-M0, SUN2000-3KTL-M1, SUN2000-4KTL-M1, SUN2000-5KTL-M1, SUN2000-6KTL-M1, SUN2000-8KTL-M1, SUN2000-10KTL-M1
Type	Integrated

Interface Protection System Adjustments (Basic Setting)

Security	Threshold of intervention	Intervention time (time between the moment the condition starts abnormal detected by the protection and the issuance of the trigger control)
Maximum voltage (59.S1, moving average measurement on 10 min, according to IEC EN 61000-4-30)	1.10 V_n	Varies depending on the start and end value of voltage, maximum 603 s.
Maximum voltage (59.S2)	1.15 V_n	0,2 s
Minimum voltage (27.S1)	0.85 V_n	1,5 s
Minimum voltage (27.S2) *	0.15 V_n	0,2 s
Maximum Frequency (81>.S1)** □	50.2 Hz	0,1 s
Minimum Frequency (81<.S1)** □	49.8 Hz	0,1 s
Maximum Frequency (81>.S2) □	51.5 Hz	0,1 s
Minimum Frequency (81<.S2) □	47.5 Hz	0,1 s

Note:

* The response time value should be used when the total power is greater than 11.08 kW, while for lower powers, an intervention time without intentional delay may be optionally used. In the case of synchronous generators, the value can be increased to 0.7 V_n e t = 0,150 s

** Threshold enabled only with external signal at high value and local command high. For voltage values below 0,2 V

□ $_n$, the maximum/minimum frequency protection should be inhibited.

Extract from test report 18TH0255-CEI 0-21_8 issued by a test laboratory accredited by Deutsche Akkreditierungsstelle GmbH (DAkkS) according to ISO/IEC 17025. The accreditation is only valid for The scope listed in the annex of accreditation certificates "D-PL-12024-03-04".

CEI 0-21: 2022-03 / V1: 2022-11 / V2: 2024-01 / V2/EC:2024 Reference technical rule for the connection of active and passive users to LV networks of energy distribution companies electric, Annex A: Interface Protection System (SPI) characteristics and tests. Annex B: Tests on grid-connected generators via static converters, Annex Bbis: Tests on storage systems				
Huawei Technologies Co., Ltd. Static Converter Manufacturer. Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129 P.R.C				
Equipment type	Photovoltaic inverters			
Static converter model	SUN2000-3KTL-M0, SUN2000-3KTL-M1	SUN2000-4KTL-M0, SUN2000-4KTL-M1	SUN2000-5KTL-M0, SUN2000-5KTL-M1	SUN2000-6KTL-M0, SUN2000-6KTL-M1
Input (DC PV)				
Voltage range MPP [V]	140-980	140-980	140-980	140-980
Max. input voltage [V]	1100	1100	1100	1100
Max. input current [A] (For SUN2000-xKTL-M1 series)	13.5H x 2 strings	13.5H x 2 strings	13.5H x 2 strings	13.5H x 2 strings
Max. input current [A] (For SUN2000-xKTL-M0 series)	11A x 2 strings	11A x 2 strings	11A x 2 strings	11A x 2 strings
Input (DC battery)				
Max. battery input voltage [V]	1100	1100	1100	1100
Max. battery current [A] (For SUN2000-xKTL-M1 series)	16,7	16,7	16,7	16,7
Max. battery current [A] (For SUN2000-xKTL-M0 series)	16,0	16,0	16,0	16,0
Connection (CA)				
Rated AC Voltage [V]	230, 3L/N/PE, 50Hz	230, 3L/N/PE, 50Hz	230, 3L/N/PE, 50Hz	230, 3L/N/PE, 50Hz
Max. output current [A]	5,1	6,8	8,5	10,1
Converter Rated Power (P_{NINV}) [kW]	3,0	4,0	5,0	6,0
Max. apparent converter power [kVA]	3,3	4,4	5,5	6,6
Battery On-grid Mode (For SUN2000-xKTL-M1 series)				
P_{sn} (nom. discharge power) [kW]	3,0	4,0	5,0	6,0
P_{cn} (nom. charging power) [kW]	3,0	4,0	5,0	6,0
P_{smax} (maximum discharge power) [kW]	3,0	4,0	5,0	6,0
P_{cmax} (max. charging power) [kW]	3,3	4,4	5,5	6,6
Types	Bi-directional	Bi-directional	Bi-directional	Bi-directional

Extract from test report 18TH0255-CEI 0-21_8 issued by a test laboratory accredited by Deutsche Akkreditierungsstelle GmbH (DAkkS) according to ISO/IEC 17025. The accreditation is only valid for The scope listed in the annex of accreditation certificates "D-PL-12024-03-04".

CEI 0-21: 2022-03 / V1: 2022-11 / V2: 2024-01 / V2/EC:2024 Reference technical rule for the connection of active and passive users to LV networks of energy distribution companies electric, Annex A: Interface Protection System (SPI) characteristics and tests. Annex B: Tests on grid-connected generators via static converters, Annex Bbis: Tests on storage systems				
Huawei Technologies Co., Ltd. Static Converter Manufacturer. Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129 P.R.C				
Equipment type	Photovoltaic inverters			
Static converter model	SUN2000-8KTL-M0, SUN2000-8KTL-M1	SUN2000-10KTL-M0, SUN2000-10KTL-M1	--	--
Input (DC PV)				
Voltage range MPP [V]	140-980	140-980	--	--
Max. input voltage [V]	1100	1100	--	--
Max. input current [A] (For SUN2000-xKTL-M1 series)	13.5H x 2 strings	13.5H x 2 strings	--	--
Max. input current [A] (For SUN2000-xKTL-M0 series)	11A x 2 strings	11A x 2 strings	--	--
Input (DC battery)				
Max. battery input voltage [V]	1100	1100	--	--
Max. battery current [A] (For SUN2000-xKTL-M1 series)	16,7	16,7	--	--
Max. battery current [A] (For SUN2000-xKTL-M0 series)	16,0	16,0	--	--
Connection (CA)				
Rated AC Voltage [V]	230, 3L/N/PE, 50Hz	230, 3L/N/PE, 50Hz	--	--
Max. output current [A]	13,5	16,9	--	--
Converter Rated Power (P_{NINV}) [kW]	8,0	10,0	--	--
Max. apparent converter power [kVA]	8,8	11,0	--	--
Battery On-grid Mode (For SUN2000-xKTL-M1 series)				
P_{sn} (nom. discharge power) [kW]	8,0	10,0	--	--
P_{cn} (nom. charging power) [kW]	8,0	10,0	--	--
P_{smax} (maximum discharge power) [kW]	8,0	10,0	--	--
P_{cmax} (max. charging power) [kW]	8,8	10,0	--	--
Types	Bi-directional	Bi-directional	--	--

Batteries that can be used with the above static converters

Brand name	Huawei	Huawei	Huawei
Technology	Li-ion	Li-ion	Li-ion
Models	LUNA2000-5KW-C0, LUNA2000-5-E0	LUNA2000-10KW-C1, LUNA2000-7-E1	LUNA2000-10KW-C1, LUNA2000-5-E1
CUS module (kWh)	5	6,9	5
BMS Firmware Version	V100R002	V200R023	V200R023
# Modules	1-6	1-6	1-6
Note: Batteries are not built into the inverter and must be installed according to local regulations.			

中华人民共和国外交部请各国军政机关对持照人予以通行的便利和必要的协助。

The Ministry of Foreign Affairs of the People's Republic of China requests all civil and military authorities of foreign countries to allow the bearer of this passport to pass freely and afford assistance in case of need.

中华人民共和国
护 照
PASSPORT

PEOPLE'S REPUBLIC OF CHINA



类型/Type	P
国家码/Country Code	CHN
护照号码/Passport No.	EJ7022355
姓名/Name	马 琳 MA, LIN
性别/Sex	男/M
国籍/Nationality	中国/CHINESE
出生日期/Date of birth	04 JUN 1980
出生地点/Place of birth	北京/BEIJING
签发日期/Date of issue	07 1月/JAN 2023
签发地点/Place of issue	北京/BEIJING
有效期至/Date of expiry	06 1月/JAN 2033
签发机关/Authority	中华人民共和国国家移民管理局 National Immigration Administration,PRC
持照人签名/Bearer's signature	马琳



1898403556

POCHNMA<<LIN<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<
EJ70223551CHN8006042M3301063MCONMBNF<<<<A950