



Radar



6 5/8" – 170 mm Radar Tool specifications

Tool OD	6 5/8" – 170 mm
Tool length (shoulder/shoulder)	8.8' – 267 cm
Thread connection pin/box	4 1/2" IF
Maximum allowed make-up torque	4 1/2" IF 24 000 ftlb – 32.5 kNm 4 1/2" IF 21 000 ftlb – 28.5 kNm Tool collar 24 000 ftlb – 32.5 kNm
Net weight	660–750 lb – 300–340 kg
Hole/drill bit size	7 7/8"–10 5/8" – 200–250 mm
Minimum bending radius	490' – 150 m
Maximum flow rate	450 gal/min – 1700 L/min
Maximum allowed inner mud pressure	1150 psi – 8000 kPa – 80 bar
Maximum allowed torque during operations	18 500 ftlb – 25 kNm
Maximum allowed push/pull (on tool housing)	75 000 lb – 35 t
Maximum allowed temperature (on tool)	158 °F – 70 °C
Maximum allowed vibration (on tool)	20 g up to 200 Hz
Electric power (input on surface)	230V-50Hz / 110V-60Hz
Electric power (output to downhole tool)	56 V DC
Recommended downhole wireline	10 or 8 AWG – 6 or 10 mm ²

Radar can only be used in combination with Drillguide GST