

M&G INDUSTRIE GmbH

Aluminium Verbundplatten **HERSTELLUNG**

The warranty conditions MGBOND are:

Processing must be carried out according to the processing instructions. Use and care are to be made considering the instructions of M & G Industrie GmbH.

Extraordinary loads and mechanical damage as well as improper care exclude the warranty.

The delamination of the aluminum cover layer shall be a contiguous area of at least 5 cm.

A complaint must be in writing, no later than 30 days after the occurrence of the defect to the seller with original proof of purchase

MGBond with visible defects must not be processed. In the case of infringement, the warranty is void.

The warranty includes:

5 years warranty for flaking, cracks and delamination, strong color changes in a short period, regardless of the normal color changes

In the case of a justified complaint, the defective plates are replaced at the manufacturer's discretion free of charge.

If a decor on the part of the manufacturer is no longer available, so equivalent replacement from the current delivery program is given.

If a warranty service is provided, the warranty period will not be extended. The warranty depends on the time value of the goods. During the entire warranty period, the replacement value compared to the replacement value of the goods is reduced annually by the percentage share based on the warranty period, every year by 15%.

A liability for further damage, consequential damage - such as costs associated with the installation and removal and transport of damaged MGBond panels - is excluded.

Provision	Property	Part of construction	Distance from sea water (m)	
			1000+	0-1000
1	Film Integrity	Non-vertical applications	$\geq 90\%$ in 5 years	No guarantee
		Vertical applications	$\geq 90\%$ in 5 years	No guarantee
2	Color change (CIElab ΔE)	Non-vertical applications	$\Delta E \leq 10$ for 5 years ($\Delta E \leq 8$ for years for whites)	No guarantee
		Vertical applications	$\Delta E \leq 10$ for 5 years ($\Delta E \leq 8$ for 5 years for whites)	No guarantee

Although it is recognized by AN (AkzoNobel) that most coatings, including Polyester Topcoats will fade and change in appearance to some degree over a period of time in outdoor installations, and that such changes may not be uniform between surfaces not equally exposed, AN warrants that the goods covered by this warranty will resist natural weathering to the extent that they will conform to the performance standards listed below during a period of ten years for vertical installations and eight years for nonvertical installations after coating for film integrity and a period of ten years for vertical installations and eight years for non-vertical installations after coating for color change, provided that all conditions of this warranty are first met. Provisions (1) through (2) below apply to buildings installed north of the 30° parallel of latitude in the northern hemisphere. Only provision (1) applies to buildings installed south of this latitude:

1. Polyester Topcoats will not peel, crack, check, or flake to an extent greater than 10 per cent of the total area, that is apparent on ordinary outdoor visual observation; and

2. Vertical installations of Polyester Topcoats will not change color more than 10 CIELAB units (8 CIELAB units for whites). Color measurements are to be made per ASTM D 2244 and only on clean surfaces removing surface deposits and chalk per ASTM D 3964.

A guarantee to third, the guarantees of the respective supplier applies.

Changes to the warranty reserved.