

MATERIAL SAFETY DATA SHEET

(Essentially Similar To Form OSHA-20) (Complies with 29CFR 1910.1200)

NEXT TO SKIN
3601-C



A Division of Southwest Lubricants
9266 Abraham Way Santee, CA 92071

DAY: (619) 449-5000
EMERGENCY 24 HOURS
CHEMTREC: 800-424-9300



SECTION I

TRADE NAME: ATV Premium 4T 10w40, PWC Premium 4T 10w40 & Snowmobile 4T 5w30
 CODE NUMBER: 33901, 33505, 14901, 14505, 15901 & 15505
 CHEMICAL FAMILY: *Petroleum Oil*

DATE 7/1/04
 SUPERCEDES 8-11-94
 C.A.S. NO. *Mixture*

TCSA INFORMATION:

SECTION II-HAZARDOUS INGREDIENTS

COMPONENTS	C.A.S. NOS.	TLV/PEL		% BY WEIGH VOLUME
		PPM	mg/m3	
Hydrotreated heavy paraffinic distillate	64742-54-7			<20
Petroleum resins	64742-16-1			<1
zinc dialkyl dithiophosphate				<2
Dimethylbenzene	1330-20-7			<1

SECTION III-FIRE AND EXPLOSION HAZARD DATA

HAZARDOUS THERMAL DECOMPOSITION Carbon Monoxide & asphyxiants	FLAMMABLE LIMITS: LEL-UEL n/a FLASHPOINT: ASTM D92 >200°C (392°F) DOT INFORMATION: oil, N.O.S.
EXTINGUISHING MEDIA: Carbon Dioxide, Dry chemical, Foam, Water Fog. <i>Avoid using Water</i>	

UNUSUAL FIRE AND EXPLOSION HAZARDS: Slightly combustible. When heated above flash point will release flammable vapors which can burn in the open or explode confined if ignited.

SPECIAL FIRE FIGHTING PROCEDURES: Do not enter any enclosed or confined area without proper protective equipment & self contained breathing apparatus.

SECTION IV-PHYSICAL DATA

BOILING RANGE: >300°C		SOLUBILITY: Neg.		PH: n/d	
VAPOR PRESSURE: <0.01mmHg @ 20°C		APPEARANCE AND ODOR: <i>Green</i> oily liquid, petroleum odor			
VAPOR DENSITY	EVAPORATION RATE	SPECIFIC GRAVITY	WEIGHT PER GALLON	% VOLATILE BY VOLUME	
Heavier THAN AIR	Less THAN ETHER	0.881		nil	

SECTION V-REACTIVITY DATA

INCOMPATIBILITY <MATERIAL TO AVOID>: Strong oxidizers	
STABILITY: stable	CONDITION TO AVOID: Do not heat above flash point.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide & asphyxiants	
HAZARDOUS POLYMERIZATION: none	occupational exposure limit: TLV = 5mg/m ³ as oil mist.

SECTION VI-HEALTH HAZARD DATA

ROUTE OF EXPOSURE	ADVERSE AFFECTS	FIRST AID PROCEDURES	NFPA
I N G	STOMACH AND/OR INTESTINAL IRRITATION, NAUSEA, VOMITTING & DIARRHEA.	DO NOT INDUCE VOMITTING. GET IMMEDIATE MEDICAL HELP. If conscience give 2 glasses water.	
I N H	RESPIRATORY IRRITATION, HEADACHE, NAUSEA, WEAKNESS, & FATIGUE. CAN CAUSE UN-CONSCIOUSNESS & RESP. ARREST.	MOVE VICTIM TO FRESH AIR. IF SYMPTOMS PERSIST GET MEDICAL ASSISTANCE. IF BREATHING STOPS, USE CPR	
E Y E	CAN CAUSE EYE IRRITATION	FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL HELP.	
A S C K I N	MAY CAUSE SWELLING AND IRRITATION.	WASH SKIN WITH SOAP AND WATER. REMOVE SOILED CLOTHING AND LAUNDRY.	
C S K I N	MAY CAUSE SWELLING, IRRITATION & DEFATTING OF SKIN.	WASH WITH SOAP & WATER. IF SYMPTOMS PERSIST, GET MEDICAL ASSISTANCE.	

<DOT> SECTION VII-SPILL OR LEAK PROCEDURES <EPA>

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE ALL SOURCES OF IGNITION. CONTAIN SPILLED MATERIAL & USE INERT ABSORBENT. USE NON-SPARKING TOOLS & COLLECT & STORE IN APPROVED CONTAINERS.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

TRANSPORTATION INFORMATION: CONSULT 46CFR PARTS 1-300 AND REFER TO SECTION III OF THIS MSDS FOR ADDITIONAL INFORMATION.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: USE NIOSH/MSHA APPROVED RESPIRATOR.

PROTECTIVE GLOVES: RECOMMENDED

OTHER PROTECTIVE EQUIPMENT: EYE PROTECTION RECOMMENDED

VENTILATION: SUFFICIENT TO MAINTAIN CONCENTRATION BELOW TLV

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTION TO BE TAKEN WHEN HANDLING OR STORING: KEEP AWAY FROM HEAT, SPARKS, FLAME OR OTHER SOURCES OF IGNITION.

PERSONAL HYGIENE: WASH WITH SOAP & WATER

OTHER PRECAUTIONS: MAINTAIN GOOD VENTILATION

APPROVED BY: Danny Massie, Director

DATE: 7/1/04

A Division of Southwest Lubricants

PRODUCT

ATV Premium 4T 10W40, PWC Premium 4T 10W40 & Snowmobile 4T 5W30

